



Description MINIATURE CIRCUIT BREAKER

Code MT 100

No. of poles 1P

No. modules 1

Rated current 20 A

Curve B

Rated voltage 230-400 V

|                                             |                                               |                                        |                                               |
|---------------------------------------------|-----------------------------------------------|----------------------------------------|-----------------------------------------------|
| Standard                                    | IEC EN 60898-1                                | Rated frequency (Hz)                   | 50/60 Hz                                      |
| Breaking capacity EN 60898 230V (Icn)       | 10000 A                                       | Breaking capacity EN 60898 (Ics)       | 0.75 x Icn                                    |
| Breaking capacity IEC/EN 60947-2 230V (Icu) | 15 kA                                         | Breaking capacity IEC/EN 60947-2 (Ics) | 50% Icu                                       |
| Insulation voltage (Ui)                     | 500 V                                         | Rated impulse withstand voltage (Uimp) | 4 kV                                          |
| Minimum operating voltage                   | 12V ac/dc                                     | Maximum operating voltage              | 440V AC / 220V DC                             |
| Electrical endurance                        | 10.000                                        | Mechanical endurance                   | 20.000                                        |
| Section rigid cable                         | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> | Section flexible cable                 | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> |
| Rated tightening torque                     | 2 Nm                                          | Operating temperature                  | -25 +70 °C                                    |
| Stocking temperature                        | -40°C + +70°C                                 | Electrocod                             | 1411                                          |

## DIMENSIONAL



## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09  
Company subject to the management and  
coordination of Polifin S.p.A.

www.gewiss.com  
sat@gewiss.com  
Last update 05/03/2026

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice