



cabur[®]

CONNECTING ENERGY
SINCE 1952

POWER SUPPLIES

CSE

Series	Number of phase	Input nominal voltage (VAC)	Input voltage range (VAC)	Input voltage range (VDC)	Output nominal voltage (VDC)	Output range (VDC)	Nominal current (A)	Power (W)	Features	Part number
EASY 1	1	120-230	85...264	127...370	24	24...28	0.42	24	-	XCSE1024W024VAA
	1	120-230	85...264	127...370	24	24...28	2.5	60	-	XCSE1060W024VAA
	1	120-230	85...264	127...370	24	24...28	3.2	77	-	XCSE1077W024VAA
	1	120-230	85...264	127...370	24	24...28	5	120	-	XCSE1120W024VAA
	1	120-230	85...264	127...370	24	24...28	10	240	-	XCSE1240W024VAA
	1	120-230	85...264	127...370	24	24...28	20	480	-	XCSE1480W024VAA
	1	120-230	85...264	127...370	48	40.5...55	10	480	-	XCSE1480W048VAA
	1	120-230	85...264	127...370	72	60...81	6.6	480	A	XCSE1480W072VAB
	1	120-230	85...264	127...370	24	24...28	40	960	A	XCSE1960W024VAA
EASY 3	3	400-500	340...550	480...780	24	24...28	10	240	A	XCSE3240W024VAA
	3	400-500	340...550	500...600	24	24...28	20	480	A	XCSE3480W024VAB
	3	400-500	340...550	500...600	48	40.5...55	10	480	A	XCSE3480W048VAB
	3	400-500	340...550	500...600	72	60...81	6.6	480	A	XCSE3480W072VAB
	3	400-500	340...550	480...780	24	24...28	40	960	A	XCSE3960W024VAA
EASY 2	1-2	230-400-500	180...550	245...780	24	24...28	2.5	60	A	XCSE2060W024VAA
	1-2	230-400-500	180...550	245...780	24	24...28	5	120	A	XCSE2120W024VAA
	1-2	230-400-500	180...550	245...780	24	24...28	10	240	A	XCSE2240W024VAA
	1-2	230-400-500	180...550	245...780	24	24...28	20	480	A	XCSE2480W024VAA



Cabur s.r.l.

Località Isola Grande, 45
17041 Altare (SV) - Italy
www.cabur.it/en



Malthe Winje