



AI, 12 Bit, U, ±10V

AI 4x U, ±10 V, 0-10 V, 1-5 V, 12 Bit

- Measuring ranges 0 ... 10 V, 1 ... 5 V, ±10 V, ±5 V, ±2.5 V, individually configurable for each channel
- Measurement resolution: 11 bit + sign
- Diagnostic messages
- Wire break detection (for 1 ... 5 V)
- Limit value alarms for each channel
- A bi-color LED (blue/red) indicates the module operating status and any malfunctions
- 4 analog inputs for measuring voltage, electrically isolated from the backplane bus
- 4 process input words

Parameters for the module

Diagnostic alarm: On | Off

Overflow/underflow diagnosis: On | Off

Representation values: SIMATIC* S7 | SIMATIC* S5 | INT16

Parameters for each channel

Wire break detection (only for 1 ... 5 V): On | Off

Interference frequency suppression: None | 10 Hz | 50 Hz | 60 Hz | 400 Hz

Measuring ranges: Deactivated | 0 ... 10 V | 1 ... 5 V | ±10 V | ±5 V | ±2.5 V

Limit value alarms enabled: On | Off

Upper/lower limit: 16 bit analog value (±27648)

Technical specifications

General information	
Order number	600-252-4AD01
Article name	AI 4x U, ±10 V, 0-10 V, 1-5 V, 12 bits
Scope of delivery	AI 4x U, ±10 V, 0-10 V, 1-5 V, 12 bits
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	4
Electrical isolation	
from the backplane bus	Yes
Between the channels	No
Internal	Max. 95 mA
Power dissipation	Max. 0.7 W
Measuring ranges / load resistance	0 ... 10 V/30 kohm, 1 ... 5 V/30 kohm, ±10 V/30 kohm, ±5 V/30 kohm, ±2,5 V/30 kohm
Measuring method	Integration
Measurement resolution	11 bit + sign

Values presentation	SIMATIC* S7 SIMATIC* S5 INT16
Interference frequency suppression	None 10 Hz 50 Hz 60 Hz 400 Hz
Refresh rate / conversion rate	Number of active channels x conversion time +16 ms for wire break detection for each channel when activated. The conversion time will depend on the interference frequency suppression: None: 8 ms 400 Hz: 45 ms 60 Hz: 109 ms 50 Hz: 128 ms 10 Hz: 342 ms
Diagnoses	Upper measuring range limit exceeded (overflow), lower measuring range limit fallen below (underflow), wire break (for 1 ... 5 V only), parameter assignment error
Process alarms	Upper and lower limit per channel
Error limits	
Operational error limit in the entire temperature range	±0.5 % relative to the nominal range
Basic error limit at 25 °C	±0.3 % relative to the nominal range
Temperature error	±0.005 %/K relative to the nominal range
Linearity error	±0.05 %/K relative to the nominal rangesv
Repeating accuracy in steady state at 25 °C	±0.05 %/K relative to the nominal range
Parameter configuration length	22 bytes
General error indicator	Red LED
Hot-swap capable	Yes
Ambient conditions	
Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-20 °C ... +80 °C
Relative air humidity	-20 °C ... +80 °C 95 % r H without condensation
Protection rating	IP 20
Certifications	CE, UL
UL	
Surrounding Air Temperature	0 °C ... +60 °C
Pollution degree	2
CE	
Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
Interference emission	DIN EN 61000-6-4 "EMC Emission"
Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock"
RoHS	Yes
REACH	Yes