



TP/.. Twisted Pair Cable

Description

Screened twisted pair cables recommended for general purpose Trend system installations. All cables are manufactured with a violet, halogen-free outer sheath with twisted pairs wrapped in an aluminium polyester tape with a tinned copper drain wire.

Features

- Violet sheath for ease of identification
- Flame retardant halogen-free sheath
- 600 V rating

Physical

TP/1/1/22/HF/200-600V. Screened single twisted pair, 22 AWG, 200 m (*Belden equivalent 8761NH).

Recommended Trend system use: Trend current loop Lan, Input/output wiring (Analogue voltage, Analogue current, Thermistor, Digital inputs and Analogue voltage outputs)



diam 4.6 mm

TP/2/2/22/HF/200-600V. Screened twin twisted pair, 22 AWG, 200m (*Belden equivalent 8723NH).

Recommended Trend system use: Trend current loop Lan



diam 5.7 mm

TP/1/1/24/HF/305-600V. Screened twin twisted pair, 24 AWG, 305 m (*enhancement of Belden equivalent 9841NH).

Recommended Trend system use: This is the cable recommended for wiring Trend networks using BACnet over MS/TP (e.g. IQeco controllers). It is important that the installation requirements detailed in the IQeco data sheet and installation instructions are followed.



diam 5.9 mm

Note: The maximum recommended length of an MS/TP segment is 1200 m (4000 feet) with AWG 18 (0.82 mm²) cross section area cable. The Trend BACnet cable is 24 AWG to simplify installation and as a result the maximum distance will be lower, the actual distance will be impacted by installation environment and network speed.

*The TP cables are of a similar construction and specification to the Belden equivalents given. However, the Trend TP cables are of a higher voltage rating (600 V) and have a halogen free sheath.

ORDER CODES

TP/1/1/22/HF/200-600V	200 m reel of screened single twisted pair 22 AWG
TP/2/2/22/HF/200-600V	200 m reel of screened twin twisted pair 22 AWG
TP/1/1/24/HF/305-600V	305 m reel of screened single twisted pair 24 AWG

SPECIFICATIONS

TP/1/1/22/HF/200-600V AND TP/2/2/22/HF/200-600V


	TP/1/1/22/HF/200-600V	TP/2/2/22/HF/200-600V
Description	Single shielded twisted pair. 22 AWG (7x30 AWG) stranded tinned copper, polyethylene insulated twisted pair - over aluminium - polyester shield with 22 AWG (7x30 AWG) stranded tinned copper drain wire, flame retardant halogen-free sheath	Two twisted pairs individually shielded. 22 AWG (7x30 AWG) stranded tinned copper, polyethylene insulation, twisted aluminium-polyester shielded pair. Cabled on common axis with a common 24 AWG (7x32 AWG) stranded tinned copper drain wire, flame retardant halogen-free sheath.
Belden equivalent	8761NH	8723NH
Trend system use	Trend current loop Lan, Trend input/output wiring (Analogue voltage, Analogue current, Thermistor, Digital inputs, and Analogue voltage outputs)	Trend Lan
Electrical Characteristics		
Maximum operating voltage	600 V RMS	600 V RMS
Velocity of propagation		65% nominal
Maximum continuous current per conductor at 25 °C	2.9 A	2.3 A
Test voltage conductor - screen	2.5 kV 3 s	2.5 kV 3 s
Test voltage conductor - conductors	2.5 kV 3 s	2.5 kV 3 s
Nominal capacitance between conductors	78.7 pF/m	
Nominal capacitance between conductor and shield (one conductor to other conductor and shield)	-	-
Nominal resistance shield	-	-
Nominal conductor DC resistance at 20 °C	52.5 ohms/km	49.2 ohms/km
Nominal impedance	-	-
Physical Characteristics		
Temperature range Installing	-15 to +70 °C	-15 to +70 °C
Temperature range Operating (Moving installation)	-15 to +70 °C	-15 to +70 °C
Temperature range Operating (Fixed installation)	-30 to +70 °C	-30 to +70 °C
Temperature range Storage	-30 to +70 °C	-30 to +70 °C
Insulation Material	Polyethylene	Polyethylene
Screen type	Aluminium/polyester 9/12 µm	Aluminium/polyester 9/12 µm
Braid	-	-
Sheath Material (colour)	Flame retardant, halogen-free (violet)	Flame retardant, halogen-free (violet)
Sheath radial thickness	0.7 mm	0.7 mm
Overall nominal diameter	4.6 mm	5.7 mm
Colour Code	black/clear	black/red, green/white
Pulling tension	158 N	187 N
Minimum bending radius	10x cable diameter	10x cable diameter
UV stability	Compliant with resistance to UV-cycle test, 1000 h, according to ASTM D 2565-99	Compliant with resistance to UV-cycle test, 1000 h, according to ASTM D 2565-99

TP/1/1/24/HF/305-600V


TP/1/1/24/HF/305-600V	
Description	Single shielded twisted pair. 24 AWG (7x32 AWG) stranded tinned copper, polyethylene insulated twisted pair . Over aluminium - polyester shield with 24 AWG (7x32 AWG) stranded tinned copper drain wire, 0.122 mm tinned copper braid and flame retardant halogen-free sheath
Belden equivalent	Enhanced version of Belden 9841NH
Trend system use	BACnet MS/TP network
Electrical Characteristics	
Maximum operating voltage	600 V RMS
Velocity of propagation	66%
Maximum continuous current per conductor at 25 °C	2.1 A
Test voltage conductor - screen	2.5 kV, 3 s
Test voltage conductor - conductors	2.5 kV, 3 s
Nominal capacitance between conductors	42.0 pF/m
Nominal capacitance between conductor and shield (one conductor to other conductor and shield)	75.5 pF/m
Nominal resistance shield	11.0 ohms/km
Nominal conductor DC resistance at 20 °C	78.7 ohms/km
Nominal impedance	120 ohms
Physical Characteristics	
Temperature range Installing	-15 to +70 °C
Temperature range Operating (Moving installation)	-15 to +70 °C
Temperature range Operating (Fixed installation)	-30 to +70 °C
Temperature range Storage	-30 to +70 °C
Insulation Material	
Screen type	Aluminium/polyester 9/23 μ
Braid	0.122 tinned copper, 90% coverage
Sheath Material (colour)	Flame retardant, halogen-free (violet)
Sheath radial thickness	0.9 mm
Overall nominal diameter	5.9 mm
Colour Code	white/blue, blue/white
Pulling tension	328 N
Minimum bending radius	10x cable diameter
UV stability	Compliant with resistance to UV-cycle test, 1000 h, according to ASTM D 2565-99

CABLE CONSTRUCTION


TP/1/1/22/HF/200-600V



TP/1/1/24/HF/305-600V



TP/2/2/22/HF/200-600V



Key:


- 1 Conductor
- 2 Insulation
- 3 Filler
- 4 Foil
- 5 Drainwire
- 6 Braiding
- 7 Sheath

DISPOSAL

COSHH (Control of Substances Hazardous to Health - UK Government Regulations 2002) ASSESSMENT FOR DISPOSAL O No parts affected.

RECYCLING ♻️

All plastic and metal parts are recyclable.



WEEE Directive:

At the end of their useful life the packaging, and product, and battery (if fitted) should be disposed of by a suitable recycling centre.

Do not dispose of with normal household waste.
Do not burn.

Please send any comments about this or any other Trend technical publication to techpubs@trendcontrols.com



© 2021 Honeywell Products and Solutions SARL, Connected Building Division. All rights reserved. Manufactured for and on behalf of the Connected Building Division of Honeywell Products and Solutions SARL, Z.A. La Pièce, 16, 1180 Rolle, Switzerland by its Authorized Representative, Trend Control Systems Limited.

Trend Control Systems Limited reserves the right to revise this publication from time to time and make changes to the content hereof without obligation to notify any person of such revisions or changes.

Trend Control Systems Limited

St. Mark's Court, North Street, Horsham, West Sussex, RH12 1BW, UK. Tel: +44 (0)1403 211888, www.trendcontrols.com