



| | | | |
|------------------------------|--|-----------------------------|---|
| Colour | Blue | Rated current (A) | 16 |
| IP degree | IP44/IP54 | No. of poles | 2P+E |
| Mechanical resistance | IK08 | Reference h | 6 |
| Rated voltage | 200-250 V | Flange dimensions (mm) | 62x62 |
| Type | 10° angled flush-mounting socket-outlet | Frequency | 50/60 Hz |
| Terminal tightening capacity | 1-2.5mm ² flexible cables - 1.5-4mm ² rigid cables | Operating temperature | -25 +55 °C |
| Type of wiring | With screw | Electrocod | 2210 |
| Glow wire test | 850 °C (active parts) - 650 °C (passive parts) | Total number of operations | > 5000 |
| Permissible overload | 22 A | Breaking capacity at 1.1 Un | 20 A |
| Insulation resistance | > 10 MΩ | Thermo-pressure with ball | 125 °C (active parts) - 80 °C (passive parts) |

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

| Saline solution | Acids | | Bases | | Solvents | | | | Mineral oil | UV rays |
|-----------------|---------------|--------------------|--------------------|-----------|-----------|-----------|-----------|------------|-------------|-----------|
| | Concentrated | Diluted | Concentrated | Diluted | Hexane | Benzol | Acetone | Alcohol | | |
| Resistant | Not resistant | Limited resistance | Limited resistance | Resistant | Resistant | Resistant | Resistant | Resistente | Resistant | Resistant |


DIMENSIONAL

TECHNICAL SYMBOLOGY

IP

IP44/IP54

IK08



-25 +55 °C



With screw

GWT

850 °C (active parts) - 650 °C (passive parts) 125 °C (active parts) - 80 °C (passive parts)



STANDARDS/APPROVALS

